



KRAMER

C-HM/RA2

High-Speed HDMI Right Angle Cable with Ethernet



C-HM/RA2 is a high-speed, 4K@60Hz (4:4:4) HDMI, cable that supports Ethernet over the HDMI line. Both ends of the cable are right angle connectors

FEATURES

Max. Resolution - 4K@60Hz (4:4:4)

High-Quality Connectors - 24K gold-plated connectors resist corrosion, and offer the best possible connectivity

Minimizes Installation Depth - The right angle design makes it the perfect cable for connecting a flat panel display to a Kramer low profile wall-plate extender when the extender is installed behind the display

Supports HDCP 2.2, HDR, deep color, x.v.Color™, Lip Sync, 7.1 PCM, Dolby TrueHD, DTS-HD, and CEC

Available Lengths - 0.9m (3ft) and 1.8 (6ft)



TECHNICAL SPECIFICATIONS

| | |
|----------------------|--|
| Video | Max Resolution 4K@60Hz (4:4:4) Max Data Rate 18 Gbps Supported Color Spaces: RGB, YCbCr, xvYCC, Adobe sRGB, sYCC601, BT.2020 HDMI Compliance: HDR, HDCP 2.2, EDID and CEC |
| Audio | Supported Audio Formats: Dolby Digital Plus™, Dolby TrueHD™, DTS–HD Master Audio™, DVD Audio, SA–CD |
| PHYSICAL | HDMI Source: On a male HDMI type A, 24K gold–plated K–Lock connector HDMI Display: On a male HDMI type A, 24K gold–plated K–Lock connector |
| CONDUCTORS | Material: Tinned Copper/Bare Copper Size: 30AWG (7/0.100) |
| SCREENING | Type: Triple shielding |
| JACKET | Material: PVC Color: Gray Diameter $7 \pm 0.15\text{mm}$ |
| MECHANICAL | Cable Bending Radius 60mm |
| ELECTRICAL | Temperature Rating: 80°C Voltage Rating: 30V Conductor Resistance: 381Ω/km MAX. at 20°C (68°F) |
| STANDARDS COMPLIANCE | Safety: Flammability Rating — VW–1 Environmental: RoHS 2.0 |





KRAMER

CONFIGURATIONS

| | |
|------------|---|
| C-HM/RA2-3 | High-Speed HDMI Right Angle Cable with Ethernet |
|------------|---|

| | |
|------------|---|
| C-HM/RA2-6 | High-Speed HDMI Right Angle Cable with Ethernet |
|------------|---|