



# KRAMER

## C-GM/GF

15-pin HD to 15-pin HD Cables

| VGA/UXGA - 15-pin HD



Kramer's C-GM/GF computer graphics video cable is a high-performance cable with molded 15-pin HD connectors on both ends. It is used for connecting computer graphics video signals between computers or video scalars and plasma, LCD or other popular display technologies

### FEATURES

**Quality Construction** - High-resolution 26 gauge mini coax for video

**Easy Installation** - Pre-terminated with molded 15-pin HD connectors, gold plated pins and thumbscrews for easy connection

**Varied Selection of Lengths** - Available in versions of 3 to 100ft (0.9 to 30.5m)

**Cable Specs** - See Kramer BC-3X2T7S for detailed cable specs



## TECHNICAL SPECIFICATIONS

---

|                           |  |
|---------------------------|--|
| Attenuation (dB/100 ft.): | -0.5dB @1MHz.-1.3dB @5MHz.-1.9dB @10MHz.-4.0dB @50MHz.-5.7dB @100MHz.-8.0dB @180MHz.-14.0dB @400MHz  |
| Conductor:                | 26 AWG 7/34 tinned copper<br>26 AWG 7/34 tinned copper   |
| Dielectric:               | Foam polyethylene with red, green, blue color coding<br>0.076in (1.95mm)   |
| Shield:                   | (A) 90% spiral 38 AWG tinned copper.(B) aluminum-foil/Mylar 25% overlap rate<br>(A) 85% braid 36 AWG tinned copper.(B) Mylar 25% overlap rate<br>(A) 85% braid 36 AWG tinned copper.(B) aluminum-foil/Mylar 25% overlap rate |
| Inner Jacket:             | PVC  |
| Jacket Colors:            | Black<br>White, white/black, red, red/black<br>Red, orange, brown, yellow, black, red/black  |
| Center Conductor:         | 0.019in (0.48mm)   |
| Individual Coax:          | 0.102in (2.6mm)  |
| Impedance:                | 75Ω  |
| DC resistance:            | 45Ω/1000ft (148Ω/km)   |
| Capacitance:              | 17.3pF/ft (57pF/m)   |
| Temperature:              | 68° to 167°F (-20° to 75°C)  |
| Jacket:                   | HD polyethylene<br>HD-polyethylene   |
| Diameter:                 | 0.34in (0.88mm)<br>0.34in (0.88mm)   |
| Conductors:               | 26 AWG 7/34 tinned copper  |
| Outer Jacket:             | PVC  |
| Outer Jacket Color:       | Dark gray w/white lettering  |
| Outer Diameter:           | 0.393in (10.0mm)   |
| UL:                       | CL2  |
| CSA:                      | C(UL) CL2  |



# KRAMER

## CONFIGURATIONS

---

|             |   |
|-------------|---|
| C-GM/GF-3   | Molded 15-pin HD (M) to 15-pin HD (F) Cable |
| C-GM/GF-6   | Molded 15-pin HD (M) to 15-pin HD (F) Cable |
| C-GM/GF-10  | Molded 15-pin HD (M) to 15-pin HD (F) Cable |
| C-GM/GF-15  | Molded 15-pin HD (M) to 15-pin HD (F) Cable |
| C-GM/GF-25  | Molded 15-pin HD (M) to 15-pin HD (F) Cable |
| C-GM/GF-35  | Molded 15-pin HD (M) to 15-pin HD (F) Cable |
| C-GM/GF-50  | Molded 15-pin HD (M) to 15-pin HD (F) Cable |
| C-GM/GF-100 | Molded 15-pin HD (M) to 15-pin HD (F) Cable |