



## VS-21TS

2x1 CAT Lines Selector with PoE

| HDBaseT



VS-21TS is a high-performance selector for Ethernet and HDBaseT CAT lines. The user selected input CAT line, either Ethernet or HDBaseT, is connected to the output CAT line with its carried signal and power

### FEATURES

**Easy Input Selection** - Click-to-connect manual selection using either panel or remote buttons

**Reliable PoE (Power over Ethernet) Powering** - Selected line remote powering is switched to input line, to provide power to its connected device

**Easy Installation** - Compact DigiTOOLS® fan-less enclosure for desktop or under-table mounting, or side-by-side mounting of 3 units in a 1U rack space with the recommended rack adapter



# KRAMER

## TECHNICAL SPECIFICATIONS

Inputs	2 Ethernet/HDBaseT CAT On RJ-45 connectors
Outputs	1 Ethernet/HDBaseT CAT On an RJ-45 connector
Signal	Max. Data Rate: 10Gbps pass-through Max. Resolution: 4K@60Hz (4:2:0) pass-through Standards Compliance: IEEE 802.3an, HDCP 2.2
User Interface	Controls: Front panel selection buttons, contact closure connectors for remote selection  Indicators: Active input and ON LEDs
Power	Source: 5V DC  Consumption: 30mA
Enclosure	Size Tool  Type Aluminum  Cooling Convection ventilation
Environmental Conditions	Operating Temperature 0° to +40°C (32° to 104°F)  Storage Temperature -40° to +70°C (-40° to 158°F)  Humidity 10% to 90%, RHL non-condensing
Product Dimensions	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H
Product Weight	0.2kg (0.5lbs) approx
Shipping Dimensions	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43" ) W, D, H
Shipping Weight	0.7kg (1.5lbs) approx

