

VP-772T

Remote Control Console with T-Bar for VP-772

| Ethernet - RJ-45



VP-772T is a dedicated remote control console for the VP-772 dual scaler seamless switcher. It is designed for use at live production events that require remote operation of the seamless switcher from a T-bar for precise switching and transition control

FEATURES

All VP-772 Functions Replicated - All the front panel controls of the VP-772 Seamless Switcher are replicated on the VP-772T

Convenient Switching Control - Via the rugged T-bar or a Take button, with selectable transition speed control

Menu Button - Control the VP-772 via an on-screen display on the preview output

Wipe Direction Control - Via front panel buttons

Control Multiple Units - Up to 4 VP-772 Seamless Switchers can be controlled from one VP-772T

2 Gooseneck Lamps - For low light environments

Control Options - 4 RS-485 ports to control up to 4 VP-772 units, and 1 RS-232 port for controlling the console

Ethernet Port - For configuration and firmware upgrade

Power Supply - 12V DC

Angled Faceplate - Enables free-standing use on a table



TECHNICAL SPECIFICATIONS

Ports 4 RS-485 on 3-pin terminal block connectors

1 RS-232 On a 3-pin terminal block connector for device control

1 Ethernet On an RJ-45 connector

User Interface Controls: Front panel buttons, T-bar, and RS-232

Power Source 12V DC

Accessories Included 2 gooseneck lamps, power adapter, rack ears, table top brackets

Product Dimensions $43.60 \text{cm} \times 17.70 \text{cm} \times 14.33 \text{cm} (17.17" \times 6.97" \times 5.64") \text{ W, D, H}$

Product Weight 1.6kg (3.6lbs) approx

Shipping Dimensions $55.00 \text{cm} \times 29.40 \text{cm} \times 16.10 \text{cm} (21.65" \times 11.57" \times 6.34") \text{ W, D, H}$

Shipping Weight 3.5kg (7.6lbs) approx

