



## Galil 4-CO

4-Inch, 2-Way Open-Back Ceiling Speakers

| Speakers



The Galil 4-CO is a pair of two-way, open-back, 8Ω speakers designed for mounting in the ceiling. The speakers feature a multi-tap power transformer for selecting 8Ω or 70V/100V power settings suitable for array installation

### FEATURES

Type - 2-way coaxial speaker

Woofers - 4" polypropylene cone

Tweeter - 0.5" Mylar dome

Frequency Response - 80Hz to 20kHz@ ±3dB

Impedance - 8Ω

Power Handling - 15W RMS, 40W continuous program

Transformer Taps - 70V: 15W/7.5W/3.7W/Off (Lo-Z); 100V: 15W/7.5W/Off (Lo-Z)

Package Includes - 2 speakers (1 pair), cutout template and user manual

Mounting Bracket (Optional) - SKIC-4



# KRAMER

## TECHNICAL SPECIFICATIONS

---

|                             |  |
|-----------------------------|--|
| DESCRIPTION:                | 2-way open-back ceiling speakers                       |
| FREQUENCY RESPONSE:         | 60Hz to 20kHz @-10dB, 80Hz to 20kHz @±3dB              |
| WOOFER:                     | 4" (103mm) polypropylene with rubber surround          |
| TWEETER:                    | 0.5" (13mm) Mylar                                      |
| IMPEDANCE:                  | 8Ω (transformer tap in off position)                   |
| TRANSFORMER TAPS:           | 70V-15W/7.5W/3.7W/Off (Lo-Z), 100V-15W/7.5W/Off (Lo-Z) |
| SENSITIVITY:                | 83dB SPL, 1W@1m  |
| MAX SPL:                    | Continuous: 95dB; peak: 98dB                           |
| POWER HANDLING:             | 15W RMS, 40W continuous program                        |
| CROSSOVER FREQUENCY:        | 13kHz  |
| COVERAGE ANGLE:             | 104°   |
| DIRECTIVITY FACTOR (Q):     | 8 averaged 1kHz to 10kHz                               |
| DIRECTIVITY INDEX (DI):     | 9dB averaged 1kHz to 10kHz                             |
| INPUT CONNECTOR:            | Terminal block   |
| MATERIALS:                  | Frame, aluminum grill, safety cord attached to grill   |
| OPERATING TEMPERATURE:      | 0° to +40°C (32° to 104°F)                             |
| STORAGE TEMPERATURE:        | -40° to +70°C (-40° to 158°F)                          |
| HUMIDITY:                   | 10% to 90%, RHL non-condensing                         |
| WEIGHT PER SINGLE SPEAKER:  | 0.95kg (2.09lbs) approx                                |
| SHIPPING WEIGHT (FOR PAIR): | 2.6kg (5.73lbs) approx                                 |
| INSTALLATION CLEARANCE:     | Mounting depth: 6.82cm (2.7")                          |
| CUTOUT DIAMETER             | 13.9cm (5.47")   |
| OPTIONAL ACCESSORIES:       | SKIC-4 installation bracket                            |
| COLORS:                     | Available in white                                     |