



## VM-22H

2x1:2 Compact HDMI Switchable DA

| HDMI | HDCP Compliant



The VM-22H is a distribution amplifier for HDMI signals. The unit reclocks and equalizes one of two selectable input signals and distributes it to two identical outputs

### FEATURES

**Max. Data Rate** - 6.75Gbps (2.25Gbps per graphic channel)

**HDCP Compliant**

**HDMI Support** - Deep Color, x.v.Color™, Lip Sync, CEC

**3D Pass-Through**

**EDID Pass-through** - Pass-through algorithm ensures Plug and Play operation for HDMI source and display systems

**Active Output LED Indicators**

**Control** - Front panel or IR remote switching

**Kramer Equalization & re-Klocking™ Technology** - Rebuilds the digital signal integrity to travel longer distances

**Compact DigiTOOLS®** - 3 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter



# KRAMER

## TECHNICAL SPECIFICATIONS

---

INPUTS:	2 HDMI connectors
OUTPUTS:	2 HDMI connectors
BANDWIDTH:	6.75Gbps (2.25Gbps per graphic channel)
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP
CONTROLS:	EDID SETUP button, input select button, IR
INDICATOR LEDs:	IN 1, IN 2, OUT 1, OUT 2, and ON LEDs
POWER CONSUMPTION:	5V DC, 910mA
INCLUDED ACCESSORIES:	Power supply, bracket installation kit, IR remote control (upon request)
OPTIONS:	HDMI/HDMI male-to-male cables
Product Dimensions	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H
Product Weight	0.3kg (0.7lbs) approx
Shipping Dimensions	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43" ) W, D, H
Shipping Weight	0.6kg (1.2lbs) approx

