



FC-332 3G HD-SDI to HDMI Format Converter

| HDMI | 3G HD-SDI - BNC



The FC-332 is a high-performance format converter for video signals up to 3G HD-SDI. The unit converts the input video format (with embedded audio) to two HDMI outputs

FEATURES

HDTV Compatible

Looping Input

Multi-Standard Operation - SDI (SMPTE 259M), HD-SDI (SMPTE 292M) and 3G HD-SDI (SMPTE 424M) compliance and support for data rates of 270Mbps, 1483.5Mbps, 1485Mbps and 2970Mbps

Embedded Audio Group Select Rotary Switch

Active Input Indication™ Reporting - Green indicates a standard definition (SDI) input signal and blue indicates a high definition (HD-SDI) input signal

Compact DigiTOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter



KRAMER

TECHNICAL SPECIFICATIONS

INPUT:	1 SD/HD/3G HD-SDI with loop on BNC connectors
OUTPUTS:	2 HDMI connectors
MAX. DATA RATE:	Up to 3Gbps
STANDARD COMPLIANCE:	HDMI
INDICATOR LEDES:	SD/HD, OUT, ON
POWER CONSUMPTION:	5V DC, 510mA
INCLUDED ACCESSORIES:	Power supply
Product Dimensions	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
Product Weight	0.3kg (0.7lbs) approx
Shipping Dimensions	23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H
Shipping Weight	0.6kg (1.3lbs) approx

