



kramer

WP-SW2-EN7

High-performance, highly-scalable, AVoIP
Wall Plate Encoder for 4K60 4:2:0 HDR10
over 1G network



WP-SW2-EN7/US-D(W) is an advanced wall plate encoder for streaming 4K@60Hz (4:2:0) video signals via Ethernet over copper cable

FEATURES

Video Streaming Transmitter - Streams up to 4K@60Hz (4:2:0) resolution signals over a 1G network interface

HDR - Supports HDR10 up to 4K@30Hz 4:2:2 12bits

Streaming Support - Unicast and multicast

Multiple Inputs - One HDMI input and one USB-C input, which support multiple switching policy including Last connected, Priority and Manually

Analog Audio Embedding - Embed the unbalanced analog audio into the streaming and HDMI output signal

Convenient and Comprehensive Control - Control the unit using intuitive web interface, protocol 3000 API commands via Ethernet, or front panel LCD and navigation buttons

Control Gateway - Through P3K or special TCP connection, user can control/communicate with RS232, CEC to the connected devices

PoE Support - Option to power with PoE connection from a PoE switch



kramer

TECHNICAL SPECIFICATIONS

Inputs	1 HDMI On a female HDMI connector 1 USB On a USB-C connector 1 Audio On a female 3.5mm mini jack
Ports	2 Ethernet On RJ-45 female connectors 1 RS-232 On a 3-pin terminal block connector
Video	Compression Standard JPEG based, private stream Max Resolution 4K@60Hz (4:2:0) or 3K@30 (4:4:4)
User Interface	Indicators HDMI, USB and ON LEDs, front panel channel display Recessed Buttons CH+, CH- and factory reset button
Power	Options 20V DC, 6A (optional, purchased separately) Consumption 20V DC, 6A Max Source PoE on LAN (PoE) port
Environmental Conditions	Operating Temperature 0° to +45°C (32° to 113°F) Storage Temperature -20° to +70°C (-4° to 158°F) Humidity 10% to 90%, RHL non-condensing
Regulatory Compliance (Standards Compliance)	Safety CE, FCC Environmental RoHs, WEEE
Enclosure	Size 2 Gang Type SGCC (galvanized steel) and PC (polycarbonate) Cooling Convection Ventilation
Product Dimensions	US: 12.10cm x 5.10cm x 12.10cm (4.76" x 2.01" x 4.76") W, D, H UK: 15.10cm x 4.00cm x 8.60cm (5.94" x 1.57" x 3.39") W, D, H
Product Weight	US: 0.4kg (1.0lbs) approx UK: 0.4kg (0.9lbs) approx
Shipping Dimensions	US: 20.00cm x 13.70cm x 7.50cm (7.87" x 5.39" x 2.95") W, D, H UK: 23.80cm x 13.70cm x 7.50cm (9.37" x 5.39" x 2.95") W, D, H
Shipping Weight	US: 0.7kg (1.5lbs) approx UK: 0.7kg (1.4lbs) approx



CONFIGURATIONS

WP-SW2-EN7/US-D(W) High-performance, highly scalable, AVoIP Wall Plate Encoder for 4K60 4:2:0, HDR10 over 1G Network, with white Decora® Design Frame Sets

WP-SW2-EN7/EU-D(W)80/86 80/86(W) High-performance, highly scalable, AVoIP Wall Plate Encoder for 4K60 4:2:0, HDR10 over 1G Network, with EU & UK White Frames

