

Dual-Port USB Wall Charger with PD Charging - USB-C (39W) & USB-A (5V 2.4A/12W)

MODEL NUMBER: U280-W02-A1C1











Dual USB wall charger quickly charges a USB-C device and a USB-A device, including tablets and smartphones, at the same time.

Features

Dual USB Wall Charger Charges 2 Mobile Devices SimultaneouslyThis dual-port USB wall charger with Quick Charge 2.0 technology lets you quickly and safely charge one USB-C mobile device and USB-A mobile device at the same time. Plug into any NEMA 1-15R, NEMA 5-15R or NEMA 5-15/20R outlet to ensure your smartphones, tablets and MP3 players, to name just a few devices, receive a satisfactory battery charge. The dual USB wall charger is compatible with Apple, Android, Windows and Amazon devices with USB-C, Thunderbolt 3 or USB-A charging ports.

USB-C PD Charging Port Supports Quick Charge 2.0 TechnologyThe USB-C port is PD 2.0 compatible, supporting Quick Charge 2.0 Class A 5/9/12V technology. Instead of charging at a preset power level, this dual-port USB wall charger adapter adjusts to provide as much power as your QC-compliant device's battery can handle. Available outputs include 5V/3A (15W), 9V/3A (27W) and 15V/2.6A (39W), which can charge your QC 2.0 device much faster than traditional chargers.

Built-In Auto-Sensing Adjusts to Proper Power LevelThe USB-A port features auto-sensing technology that detects the connected device and automatically adjusts to the appropriate power level up to 5V 2.4A, perfect for fast-charging tablets and e-readers.

Folding Plug Design Perfectly Sized for TraveIThe dual USB travel charger is easy to carry in your purse, suitcase, backpack or laptop bag. The NEMA 1-15P plug folds into the unit when not in use to shield it from damage and prevent it from snagging or scratching your bag's contents.

Specifications

OVERVIEW		
UPC Code	037332214416	
Product Type	Wall Charger	
Charging Form Factor	Direct Plug-In	

Highlights

- Ideal for charging smartphones, tablets, e-readers and MP3 players while traveling
- USB-C PD Charging port supports Quick Charge 2.0 Class A 5/9/12V technology
- Auto-sensing USB-A port adjusts charging power level to your device up to 5V 2.4A
- Maximum charging power output of 51W: 39W USB-C and 12W USB-A
- Plug folds inward to protect it from damage and help the unit fit into a purse or bag

Applications

 Charge up to 2 smartphones, tablets, cameras, e-readers or any other USB-C, Thunderbolt 3 or USB-A devices

Package Includes

 U280-W02-A1C1 Dual-Port USB Wall Charger with PD Charging



Device Compatibility	Phone; Tablet; Amazon Kindle; Laptop; Chromebook	
INPUT		
Nominal Input Voltage(s) Supported	120V AC; 230V AC	
Input Connection Type	NEMA 1-15P	
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240	
Input Frequency	50/60Hz	
Input Plug Type	NEMA 1-15P (NON-POLARIZED)	
Input Current	1.5A	
OUTPUT		
Output Capacity	51W	
Overload Protection	Yes	
CHARGING		
Number of Charging Ports	2	
Total Charging Amps	1.5A	
Total Charging Watts	51	
Charging Method	USB	
Charging Port Type	USB A (FEMALE); USB C (FEMALE)	
Charging Ports Details	USB-C: 39WUSB-A: 5V 2.5A (12W)	
Charging Ports / Amps	(1) 2.4A; (1) 3A / 2.6A	
Charging Method Detail	Power Deliver 2.0; Quick Charge 2.0	
PHYSICAL		
Material of Construction	Plastic	
Color	Black	
Shipping Dimensions (hwd / cm)	3.71 x 14.00 x 13.59	
Shipping Dimensions (hwd / in.)	1.46 x 5.51 x 5.35	
Shipping Weight (kg)	0.19	
Shipping Weight (lbs.)	0.41	
Unit Dimensions (hwd / in.)	2.9 x 2.5 x 1.2	
Unit Dimensions (hwd / cm)	7.5 x 6.3 x 3	
Unit Packaging Type	Вох	
Unit Weight (lbs.)	0.30	
Unit Weight (kg)	0.14	





ENVIRONMENTAL		
Operating Temperature Range	32 to 95 F (0 to 35 C)	
Storage Temperature Range	-4 to 185 F (-20 to 85 C)	
Operating Humidity Range	30 TO 90% RH, Non-Condensing	
Storage Humidity Range	10 TO 90% RH, Non-Condensing	
CONNECTIONS		
Number of Ports	2	
Side A - Connector 1	NEMA 1-15P (NON-POLARIZED)	
Side B - Connector 1	USB A (FEMALE); USB C (FEMALE)	
FEATURES & SPECIFICATIONS		
Over Current Protection	Yes	
Driver Required	No	
Quick Charge Compliant	No	
Overcurrent Protection	Yes	
Overvoltage Protection	Yes	
GaN Technology	No	
STANDARDS & COMPLIANCE		
Product Certifications	UL Listed	
Product Compliance	RoHS; REACH; FCC (USA)	
WARRANTY		
Product Warranty Period (Worldwide)	2-year limited warranty	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies