



Side view

Vandal-resistant intercom station with call switch features a heavy duty stainless steel wall plate and vandal-resistant screws with driver bit. The station is ideally suited for areas where vandalism may be a concern such as correctional facilities, public garages, lobbies, warehouses and similar areas.

### FEATURES:

- **Wall Plate:**
  - Heavy duty 11-gauge stainless steel two-gang wall plate with brushed finish.
  - Shallow depth, can mount in a standard two-gang box
  - Internal offset baffles provide added protection from vandalism.
  - Includes vandal-resistant hardware for a high degree of security. (Torx head screws and driver bit)
- **Speaker:**
  - 45ohm, 6W, 98dB @1W, 300Hz-8kHz
  - Moisture resistant
  - Pigtail connections for easy field installation
  - For clear one-way or two-way communication
- **Transformer:**
  - 25V line 1W, 1/2W
  - Pigtail connections

### • Call Switch:

- SPST (single pole, single throw)
- Rating: 1A 48VDC
- Function: Momentary (normally open)
- Screw terminal connections

### A&E SPECIFICATIONS:

The vandal-resistant intercom station with call switch shall be Lowell VRIC-2G-4525, which shall feature a 45ohm speaker with 25V transformer and a push button call switch. The intercom station shall have two-gang wall plate, 11-gauge stainless steel with brushed finish. The unit shall feature offset baffles and include vandal-resistant screws and a driver bit.

### OPTIONS: (order separately)

- **PHB-2 Hooded Box:** Protective hooded two-gang box, 11-gauge steel with gray finish. 4.50"H x 4.625"W x 4.0"D
- **P1X-2 Box:** Surface-mount two-gang box, 20-gauge steel with knockouts, white finish. 4.625"H x 4.625"W x 2.5"D



### VRIC Intercom Series Overview

Model No.	Description	Wall Plate	Speaker	Transformer	Height	Width	Depth
<b>VRIC-2G-4525</b>	<b>Intercom station w/call switch</b>	<b>2-gang</b>	<b>45 ohm</b>	<b>25V</b>	<b>4.5"</b>	<b>4.47"</b>	<b>1.75"</b>
VRIC-3G-4525	Intercom station w/call switch	3-gang	45 ohm	25V	4.5"	6.375"	1.75"

This spec

