



Novanex Model OAX2-EC

PoE Emergency Messaging Display with Day/Date Clock

Our Power over Ethernet Emergency Messaging Display / Clock is visible from 150' (45.72m) in single line mode and 90' (27.43m) in two line mode, and displays the day, date, time and text on one or two lines. Send text from a web page or integrate to major mass notification providers. Made in the USA by Novanex, US and imported components. 5 year warranty.

Specifications

LED Characteristics	16 x 96 pixel array; 3 colors (red, yellow, green) 5mm (.02") diameter, 7.62mm (.03") spacing
Case Material and Dimensions	Black powder-coated aluminum case, non-glare polycarbonate lens 7" H x 36" W x 1.75" D (17.8cm x 91.5cm x 4.5cm)
Weight	6 lbs.
Mounting	VESA 100mm tilt wall mount bracket included
Presentation Modes	Scroll up, ribbon left, disappear, others
Characters	Two-line mode: 2" height, 18 per line Single line mode: 4.1" height, 8 per line
Operating Environment	Temperature 32-104 F (0-40 C) Humidity: 95% max, non-condensing
Network Interface	10/100 BaseT Ethernet NIC, SSH configuration, DHCP or static addressing, MAC Address label with barcode
DHCP Support	Standard options; Option 42, 100
Operating Voltage	IEEE 802.3af Power over Ethernet (PoE, PoE+) compatible, 11 watts, RJ-45
Timekeeping	SNTP, +/- 200ms
Speaker	Volume: 74.5 dBA @ 1 meter
Alerting Light	Amber color, 11 lumens after filtering, flashing configurable
Standards	UL/CSA 60951-1, ETL listed, CE marked