

Valcom InformaCast® compliant IP Speakers enable you to send live, prerecorded or ad hoc audio messages over your new or existing multicast enabled network.

A wide variety of Valcom InformaCast enabled IP speakers ensure an attractive and effective solution for every environment such as offices, meeting rooms, gymnasiums, warehouses, hallways and outdoor areas. All control of the loudspeaker audio and clock functionality is determined via software control.

- InformaCast & InformaCast CK compliant
- Operates with Cisco VoIP networks, phones and InformaCast
- Web-based configuration
- Easy to install via RJ-45 Ethernet
- PoE (802.3af) No local power required
- Multicast enabled
- Operating temperature -30 to +55C (-22 to +131F)
- Compatible with text/audio to IP Telephones
- Use web (HTTP) interfaces for status and configuration
- Synchronized clocks
- DHCP
- Web based firmware upgradeable for future needs
- Made in USA

Valcom complies with requirements of the Buy America Act provisions of the American Recovery and Reinvestment Act of 2009.

IP PAGING GATEWAYS



Audio Ports

- 1 Audio Port NETWORKED.....VIP-801-IC
- Single Port - Valcom VIP-801-IC
 - Line Level Audio Out
 - Contact Closure Out
- Dimensions: 1.38" H x 6.13" W x 5.25" D

Backbox Selection Chart

Type	Part No.	Mount Style	Dimensions
11	VB-S11	Surface	11.63"H x 11.63"W x 3.94"D Grille Hole Dimns.: 10.00" x 10.00"
12	VB-R12	Recessed	10.75"H x 10.75"W x 3.94"D Grille Hole Dimns.: 10.00" x 10.00"
13	VB-A13	Angled	11.54"H x 11.63"W x 4.60"D Grille Hole Dimns.: 10.00" x 10.00"
16	VB-R16	Recessed	7.50"H x 9.84"W x 3.94"D Grille Hole Dimns.: 6.50" x 9.00"
17-D	VB-R17-D	Recessed	9.63"H x 9.63"W x 5.94"D Grille Hole Dimns.: 8.88" x 8.88"
19	VB-R19	Recessed	19.25"H x 10.75"W x 3.75"D Grille Hole Dimns.: 10.00" x 18.50"
20	VB-S20	Surface	20.18"H x 14.27"W x 2.78"D Grille Hole Dimns.: 10.00" x 18.50"
21	VB-A21	Angled	19.88"H x 14.37"W x 5.50"D ¹ x 2.71"D ² Grille Hole Dimns.: 10.50" x 18.50"
22	VB-R22	Recessed	13.25"H x 11.25"W x 3.94"D Grille Hole Dimns.: 10.50" x 12.50"
23	VB-S23	Surface	14.63"H x 13.13"W x 3.94"D Grille Hole Dimns.: 10.50" x 12.50"
24	VB-A24	Angled	14.41"H x 13.13"W x 5.00"D ¹ x 3.00"D ² Grille Hole Dimns.: 10.50" x 12.50"

PoE — No External Power Needed!



Integral Clock/Speakers
Use Only One Switch Port

Talkback or One-Way
Paging Applications



IP CEILING & WALL SPEAKERS

IP CLOCK/SPEAKERS

IP HORNS



- PoE (802.3af) - No Local Power Required
- 2.5" - 5 Character
- Red LED's, Other LED Colors On Request
- Only One Ethernet Port Connection Required
- Output Level 103 db/1Meter
- Aux Output Supports Valcom Amplified Speakers
- Mounting Backboxes Available *See Backbox Chart on Back Page.
- Valcom offers a line of stand alone IP PoE clocks, visit www.valcomclocks.com

	One-Way	Talkback	Backbox Type*
A. IP Ceiling Round 8" Speaker White Dimensions: 12.88" H x 12.88" W x 4" D • 103db/1Meter	VIP-120-IC	VIP-160-IC	V-9816M
B. IP 2' x 2' Lay-In Ceiling Speaker White Dimensions: 23.75" H x 23.75" W x 4.25" D	VIP-402-IC	VIP-422-IC	Included
C. IP 1' x 2' Lay-In Ceiling Speaker White Dimensions: 23.75" L x 11.75" W x 3.75" D • Easy/Fast Installation	VIP-401-IC	VIP-421-IC	Included
D. IP Wall Speaker Assembly Gray w/Black Grille Dimensions: 10.13" H x 12.31" W x 4.63" D ¹ x 1.5" D ²	VIP-410-IC	VIP-430-IC	N/A
E. IP Square Faceplate 8" Speaker White Dimensions: 11.5" H x 11.5" W x 3.125" D	VIP-418-IC	VIP-428-IC	11, 12, 13

	One-Way	Talkback	Backbox Type*
F. IP Speaker Faceplate Unit w/Digital Clock White Dimensions: 14.5" H x 13" W x 2.625" D	VIP-419-D-IC	VIP-429-D-IC	22, 23, 24
G. IP Speaker Angled Surface Mount w/Digital Clock Gray w/Black Grille Dimensions: 15" H x 12.25" W x 4.00" D ¹ x 1.45" D ²	VIP-411-DS-IC	VIP-431-DS-IC	N/A
H. IP Speaker Faceplate Unit w/Digital Clock Gray w/Black Grille Dimensions: 20.29" H x 14.38" W x 3.75" D	VIP-412-DF-IC	VIP-432-DF-IC	19, 20, 21
I. IP Speaker Faceplate Unit w/Analog Clock White Dimensions: 20.29" H x 14.38" W x 3.75" D		VIP-431-A-IC	19, 20,



- PoE (802.3af) - No Local Power Required
- Very High-Efficiency Ensures Penetration with Lower Energy Consumption
- Weather-Resistant
- L Versions Include Long Line Extender for Cabling Up to 1200 Feet
- Backboxes Available for Some Speakers

*See Backbox Chart on Back Page.

	One-Way	Talkback	Backbox Type*
J. IP Horn Dimensions: 7.38" H x 10.0" W x 10.4" D • 117db/1 Meter • Interior or Exterior Colors: Beige -BGE, Gray -GY, Marine White -W (Add Suffix to Part No.)	VIP-130L-IC	VIP-148L-IC	Protective Wire Cage V-WGHORN
K. IP FlexHorn Dimensions: 6.8" H x 8.3" W x 3.3" D • Water-Proof • Interior or Exterior • Includes Easy Adjustable Mounting Bracket Colors: Beige -BGE, Gray -GY, White -W (Add Suffix to Part No.)	VIP-480L-IC	N/A	Protective Wire Cage V-WGFLEX
L. IP FlexHorn Square Faceplate White Dimensions: 10.75" H x 10.75" W x 4.00" D • Interior or Exterior	VIP-9880-IC	N/A	17D
M. IP FlexHorn Surface Mount Unit Lt. Gray Dimensions: 10.0" H x 12.12" W x 4.00" D • 114db/1 Meter • Interior or Exterior	VIP-580-IC	N/A	N/A
N. IP FlexHorn Angled Surface Mount Unit Lt. Gray Dimensions: 10.00" H x 12.12" W x 4.00" D ¹ x 3.00" D ² • 114db/1 Meter • Interior or Exterior	VIP-581-IC	N/A	N/A
O. IP FlexHorn Stainless Steel Grille Vandal-Resistant Dimensions: 8.50" H x 11.00" W x 3.90" D • 114db/1 Meter • Interior or Exterior	VIP-483-IC	N/A	16