

WALL MOUNT VOLUME CONTROL MODEL V-1092

FEATURES:

BRUSHED STAINLESS STEEL PLATE

EMBOSSSED MARKINGS FROM 0 TO 10

WALL MOUNTABLE

SINGLE GANG SURFACE MOUNT BOX INCLUDED

CONTROLS VOLUME OF UP TO 150 ONE-WAY SPEAKERS



DESCRIPTION:

The V-1092 permits adjusting speaker volume from a convenient wall mounted location. The volume control features a stainless steel plate with embossed numbers and fits a single gang electrical wall box. The wall mount volume control controls volume of up to 150 one-way self-amplified speakers.

SPECIFICATIONS:

CAPACITY:

Controls volume of up to 150 one-way self-amplified speakers

HOUSING AND FINISH:

Brushed stainless steel single gang plate with raised number dial scale; skirted black knob and position indicator; includes stainless steel mounting box.

MOUNTING:

The V-1092 can be mounted in wall or on surface using a single gang electrical box.

DIMENSIONS AND WEIGHT:

4.5" (11.43 cm) H x 2.75" (6.99 cm) W x 2.8" (7.11 cm) D

Weight: 0.8 lb (.36 kg)

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS MODEL V-1092 WALL MOUNT VOLUME CONTROL

The Wall Mount Volume Control, Model V-1092, shall be capable of controlling the volume of up to 150 one-way self-amplified speakers. It shall be mounted on a brushed stainless steel single gang wall plate. The plate shall be embossed with a dial scale of "0 through 10." It shall be equipped with a skirted black knob with white position indicator. It shall include a stainless steel mounting box and hardware.

Dimensions shall be 4.5" (11.43 cm) H x 2.75" (6.99 cm) W x 2.8" (7.11 cm) D. Weight shall be approximately 0.8 lb (.36 kg).

Limited Warranty

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the replacement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Valcom, Inc. indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened.
(A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Valcom, Inc. are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs
(major repairs will be subject to additional charges for parts and labor).

This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event shall Valcom, Inc. be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.