

# Singlewire InformaCast IP66 Outdoor Horn

**CyberData**

The IP Endpoint Company

The new Singlewire InformaCast IP66 Outdoor Horn provides an easy method for implementing a loud IP-based overhead paging system for loud areas, warehouses, manufacturing areas, and outdoor areas.

Now with up to 9 user-stored messages.

The interface is compatible with most SIP-based IP PBX servers that comply with the SIP RFC 3261. For non-SIP environments, the speaker can be configured to listen to multicast address and port number combinations to form paging zones.

## Can receive pages directly from Polycom phones

### Features

- SIP Enhanced interoperability for hosted environments
  - CyberData has maintained one of the most comprehensive list of IP PBX servers certified to work with CyberData
- NEW SECURITY FEATURES:
  - Support for security code access for SIP paging
  - Autoprovisioning via HTTPS
  - HTTPS web based configuration
- Support for G.711, G.722, G.729 codecs
- 802.11q VLAN tagging
- Configurable event generation for device health and status monitoring
- 9 user-uploadable page messages
- IP66-rated
- Sealed network cable gland
- SIP and Simultaneous Multicast
- Page from Polycom phones
- Dual-speed ethernet 10/100 Mbps
- Web-based configuration
- PoE 802.3at and 802.3af-enabled
- User-uploadable tones and messages
- Digital volume control
- Second SIP endpoint "Night Ringer"
- Autoprovisioning
- HTTP Command Interface
- 10 channel prioritized Multicast ports
- Built-in diagnostics
- Delayed page support
- Cisco SRST

### Singlewire InformaCast Features

- Singlewire Informacast compatibility available.
- Includes support for Informacast resiliency.
- Supports both SIP and Singlewire InformaCast
- InformaCast compliant
- InformaCast CK compliant



### Specifications

|                     |                                                                                                                                                                                |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ethernet I/F        | 10/100 Mbps                                                                                                                                                                    |
| Protocol            | InformaCast and SIP RFC 3261 Compatible                                                                                                                                        |
| Power Input         | PoE 802.3at or 802.3af                                                                                                                                                         |
| Audio Output        | 802.3at: 107.7 (+/- 0.2) dBC @ 1M and 1kHz<br>802.3af: 104.8 (+/- 0.2) dBC @ 1M and 1kHz                                                                                       |
| Operating Range     | Temperature: -40° C to 55° C (-40° F to 131° F)<br>Humidity: 5-95%, non-condensing                                                                                             |
| Storage Temperature | Temperature: -40° C to 70° C (-40° F to 158° F)                                                                                                                                |
| Storage Altitude    | Up to 15,000 ft. (4573 m)                                                                                                                                                      |
| Payload Types       | G.711 a-law, G.711 µ-law, G.722, G.729                                                                                                                                         |
| Dimensions*         | Length: 4.404 in. [366 mm]<br>Width: 10.630 in. [270 mm]<br>Height: 6.772 in. [172 mm] (without stand)<br>Height: 9.291 in. [236 mm] (with stand)                              |
| Weight              | 6.6 lbs. [3 kg]                                                                                                                                                                |
| Compliance          | CE; EMC Directive – Class A EN 55032 & EN 55024, LV Safety Directive – EN 60950-1, RoHS Compliant, FCC; Part 15 Class A, Industry Canada; ICES-3 Class A, IEEE 802.3 Compliant |
| Warranty            | 2 Years Limited                                                                                                                                                                |
| Part Number         | 011472                                                                                                                                                                         |

\*Dimensions are measured from the perspective of the product being upright with the front of the product facing you.

# Singlewire InformaCast IP66 Outdoor Horn

